# Determination of Plastic Limit by Fall Cone Test for Soils with Different Grain Size Distribution

Murat Gulen<sup>1\*</sup>, Oguzhan Saltali<sup>2</sup>, Havvanur Kilic<sup>3</sup>

<sup>1</sup> Department of Civil Engineering, Faculty of Engineering, Siirt University, University Street, 56100 Siirt, Türkiye

<sup>2</sup> Department of Civil and Environmental Engineering, Michigan State University, 428 S. Shaw Lane, MI 48824 East Lansing, Michigan, USA

<sup>3</sup> Faculty of Civil Engineering, Yildiz Technical University, Davutpasa Street, 34220 Istanbul, Türkiye

\* Corresponding author, e-mail: murat.gulen@siirt.edu.tr

Received: 15 August 2024, Accepted: 24 March 2025, Published online: 14 April 2025

#### Abstract

Compaction parameters and consistency limits are fundamental engineering properties considered in the design of geotechnical applications. It is important to compare these parameters derived from experimental studies with the equations proposed in the literature or alternative methods. This study determined the plastic limit values of soils with different grain size distributions and different consistency limits using the relationship between penetration depth and water content from the fall cone test, employing a cone with 30° and 80 g characteristics. The method for determining the plastic limits has been developed based on a wide range of data. It defines the water content corresponding to a 3 mm penetration of the cone into the soil as the plastic limit. The plastic limit values determined by the proposed method were tested with a comprehensive dataset compiled from literature studies. The results indicated a satisfactory correlation between the plastic limits determined by the tread rolling method and those determined by the proposed method ( $R^2 = 0.76$ ). Furthermore, the compaction parameters obtained from the standard compaction tests were investigated using univariate and multivariate regression analyses, with consideration given to the liquid and plastic limits determined from the fall cone tests. The findings indicate that the compaction parameters can be predicted with high coefficients of determination ( $R^2 = 0.89$ ) using the plastic and liquid limits determined from the relationship between water content and penetration depth in the fall cone tests.

## Keywords

modified plastic limit, fall cone test, penetration depth, water content, compaction parameters

## **1** Introduction

Soils with different grain size distributions and consistency limits are commonly utilised as backfill materials in geotechnical applications, including earth embankments, dams, road embankments, and solid waste storage facilities. The engineering properties of soils, including specific gravity (Gs), plastic limit (PL), liquid limit (LL), plasticity index (PI), maximum dry unit weight (MDW), optimum water content (OWC), undrained shear strength (Cu), sensitivity of clays (St), degree of saturation (Sr), grain size distributions, and mineralogy, are employed to assess the suitability of these soils.

The liquid limits of cohesive soils are mostly determined using the Casagrande apparatus developed by Casagrande [1] and known by its name, besides the fall cone device developed by Olsson [2]. According to some researchers, the fall cone liquid limit  $(LL_{FC})$  value is more reliable and realistic than the Casagrande liquid limit  $(LL_{CUP})$  value since the former is more independent of the tester than the latter [3–6]. Comparing the liquid limits determined from such tests, the LL is close to each other for the soils with LL less than 100%, while significant differences are observed between LL for the soils with LL greater than 100% [7–10].

According to the cone angle and weight, the  $LL_{FC}$  values determined using a fall cone with different properties and the penetration depth (*h*) corresponding to such  $LL_{FC}$  can differ as shown in Table 1 [11–20]. The fall cone features in Table 1 are defined by relevant standards, which are considered in literature studies. The penetration depth ( $h_L$ ) of 10 mm is generally accepted for the  $LL_{FC}$  value from the fall

		Table 1 The fall e	one test standar	as of afficient	eodifitiles	
Cone properties						Cone penetration
Reference	Country	Standard	Angle (°)	Mass (g)	during the interpretation	depth at the LL <sub>FC</sub> (mm)
[11]	Sweden	SS 027120	60	60	$\log h - w$	10
[12]	Norway	NS 8002	60	60	$\log h - w$	10
[13]	Japan	JGS 0142	60	60	h-w	11.5
[14]	India	IS 2720-5	31	148	h-w	20
[15]	UK	BS 1377-2	30	80	h-w	20
[16]	New Zealand	NZS 4402	30	80	h-w	20
[17]	France	NF P 94-052-1	30	80	h-w	17
[18]	China	SL237-007	30	76	$\log h - \log w$	17
[19]	Russia	GOST 5184	30	76	h-w	10
[20]	Australia	AS 1289	30	80	h-w	20

Table 1 The fall cone test standards of different countries

cone having a cone 60° and 60 g configuration, whereas the  $h_{I}$  of 20 mm is commonly used for the  $LL_{FC}$  value of the fall cone with 30° and 80 g. Kumapley and Boakye [21] state that while the h<sub>L</sub> value changes in the range of 10-12 mm in soils with LL less than 90% for a cone of 60° and 60 g, Japanese Geotechnical Society [22] expresses the h<sub>r</sub> value as the water content (w) corresponding to 11.5 mm penetration. Two different methods determine the liquid limits of the soils, while the plastic limits are determined only by the tread rolling method. For this test, soil is mixed with water until it becomes plastic and easily molded into a ball. An 8-10 g sample is then rolled by hand on a glass plate until it crumbles at a 3.2 mm diameter. This process is repeated three times per sample, and the water content at crumbling is recorded as the PL. It should be noted that the plastic limits determined through the tread rolling method are highly dependent on the operator's experience. Thus, the PL value may exhibit variability when performed under identical conditions. This has led to the necessity of determining the PL using alternative methods. Several researchers have derived the PL value from the w-h relationship obtained from the fall cone test [23, 24].

Notedly, Wood and Wroth [24] indicated that if a single test determined the PL and LL values of soils, these values would be considerably easier, more useful, and more meaningful. In this context, they showed that the PL value can be calculated with empirical equations developed by the *h*. Koumoto and Houlsby [23] accepted the *w* value corresponding to 1.15 mm penetration depth as the PL for the fall cone having a cone of  $60^{\circ}$  and 60 g configuration. No penetration value corresponding to the PL value for the fall cone with the properties of  $30^{\circ}$  and 80 g has not been proposed in the literature.

The relationships between consistency limits and other engineering properties have been the focus of investigation by various researchers. One of the earliest studies to examine the relationship between compaction parameters and consistency properties was carried out by Jumikis [25]. Ring et al. [26] proposed equations for predicting MDW and OWC using the PL, LL, PI, median diameter (D<sub>50</sub>), and fine content. Nagaraj et al. [3] determined the modified compaction parameters (MPP) and consistency limits using a total of 42 cohesive natural soils with grain sizes less than 0.425 mm and greater than 0.425 mm and having different consistency properties. It was suggested that the modified plastic limit (MPL) value could be calculated by considering the soils with grain sizes larger than 0.425 mm sizes larger than 0.425 mm, and they also made suggestions for determining the MPP values using the MPL value. Blotz et al. [4] and Gurtug and Sridharan [5] determined the compaction parameters of cohesive soils with different consistency properties by considering the PL, LL, and different compaction energy levels. When the studies on the estimation of compaction parameters using consistency limits are examined, three views are commonly employed on the topic. While Nagaraj et al. [3], Sridharan and Nagaraj [6], Sivrikaya et al. [7], and Jyothirmayi et al. [8] stated that the compaction parameters exhibited a better correlation with the PL value, Ng et al. [9], Saikia et al. [10], Gurtug et al. [27], Hussain and Atalar [28], and Fondjo et al. [29] underlined the compaction parameters exhibited a better correlation with the LL value. According to other researchers, employing the PL and LL values together resulted in a higher correlative relationship [30-33]. The compaction parameters are expressed as a function of PL, LL, PI, Gs, and grain size distributions. Thus, a comprehensive data set

was constituted as a result of the studies in the literature. The data were evaluated using various multivariate analysis methods, including, regression analyses, SPSS, and artificial neural networks [7, 30–36].

This study developed a method that considers the relationship between *h* and *w* to determine the plastic limit value ( $PL_{FC}$ ) for soils with different grain size distributions and consistency limits from the fall cone test with 30° and 80 g properties. The  $PL_{FC}$  values were tested using a comprehensive data set from the literature. Furthermore, the compaction parameters of soils with different grain diameter distributions were predicted by univariate and multivariate regression analyses utilising the  $PL_{FC}$  and  $LL_{FC}$  values obtained from a single test device. In particular, the compaction parameters for the  $PL_{FC}$  and  $LL_{FC}$  values can be determined based on the comparisons performed by examining an extensive database comprising 594 data resources.

#### 2 Material and methods

A total of 83 natural cohesive soil samples with different index properties were supplied from various regions of Turkey (Kocaeli, Bilecik, Isparta, Karaman, Burdur, Trabzon, Tokat, and Erzincan), notably from Istanbul. The PL, LL, Gs, and grain size distribution of each soil sample were determined at the Yildiz Technical University Geotechnical Engineering Laboratory. Fig. 1 shows the plasticity chart of the soils in which the  $LL_{FC}$  values are in the range of 22.5% and 121.4%, determined by the fall cone with 30° and 80 g, the PL values between 16% and 63.5% by the thread rolling method and the PI values calculated as  $LL_{FC}$ -PL vary between 12.57% and 63.76% according to British Soil Classification System (BSCS).



Fig. 1 Soils in the scope of this study

The classification distributions for these soils are presented by the following specifications: MI (5 soils), MH (19 soils), MV (16 soils), ME (4 soils), CL (12 soils), CI (12 soils), CH (9 soils), CV (4 soils), and CE (2 soils). As depicted in Fig. 2, the *h* ranged between 1.96 mm and 29.62 mm, and the *w* values were 7.56% and 135% in the fall cone tests performed at an average of 6 points for 83 cohesive soils with different consistency properties. Soil samples prepared with 6 different *w* values for each soil were kept in a humidity cabinet for 24 h. The samples were made more homogeneous by mixing at regular intervals for 24 h. Furthermore, it was ensured that at least three points of the *h* values obtained from the fall cone test, corresponding to the six distinct water contents, were situated between 15 and 25 mm.

In the present study, the  $PL_{FC}$  was determined by reference to the *w* and *h* relationship obtained from the fall cone tests and by the following steps (Fig. 3). Fig. 3 (a), the line that best fits these points on the double logarithmic axis was determined for six different *w* and *h* values for each soil. Following the:

- (1) process step, the 20 mm penetration value is extended with this slope line in the vertical direction. The value of this point on the y- axis is determined by following the LL<sub>FC</sub>,
- (2) process step. After determining the LL<sub>FC</sub> value, the slope line drawn for 6 different w and h is extended to the y-axis by following the procedure step,
- (3) The PL value determined by the tread rolling method for each soil is extended to the trend line by following the process step,



Fig. 2 The range of h and w for fall cone test



**Fig. 3** Determination of  $PL_{FC}$  (a) determination of the  $LL_{FC}$  and extension of the slope line, (b) determination of the  $h_p$  corresponding to PL, (c) the  $PL_{FC}$  corresponding to the  $h_{pave}$ 

- (4) on this double-sided logarithmic axis. The value of this intersection point on the x-axis is determined by following the process step,
- (5) and this penetration depth (h<sub>p</sub>) on the x-axis is determined (Fig. 3 (b)). These steps were repeated for each soil, and 83 different h<sub>p</sub> depths were determined. An average penetration depth (h<sub>pave</sub>) was computed by taking the arithmetic average of the h<sub>p</sub> values determined for each of the 83 soils. In the Fig. 3 (c), the water content value corresponding to the h<sub>pave</sub> value determined by following steps,
- (6) and (7) was determined, and this value was called the modified plastic limit (PL<sub>FC</sub>).

The steps displayed in Fig. 3 were repeated for each of the 83 soils, and the  $h_p$  and the PL distribution were plotted on the histogram in Fig. 4. When all data were analysed, the arithmetic mean of the  $h_p$  depths within the range of 1 mm and 5.6 mm equals 3 mm.

## 2.1 Determination of compaction parameters

Among 83 cohesive soils, 23 natural soils with  $LL_{FC}$  values ranging from 22.5% to 121.4% were used in the compaction tests. After that, standard compaction tests were performed on a total of 46 soils (3 SC-SM soils, 8 SC soils, 6 CL soils, 10 CI soils, 5 CH soils, 2 CV soils, 6 MH soils, and 6 MV soils) by adding different proportions of sand and gravel to these 23 soils. The soil properties presented in Table 2 were determined by preliminary laboratory



Fig. 4 Distribution of the penetration depths corresponding to the PL

	Cor	nsistency lim	iits	Grai	n size distrib	ution		Compactio	n parameters	Soil type (BSCS)
Soil ID	LL	PL	LL <sub>FC</sub>	$\mathbf{G}^1$	$\mathbf{S}^2$	$M^3$	$C^4$	OWC	MDW	
	(%)	(%)	(%)	(%)	(%)	(%)	(%)	(%)	(kN/m <sup>3</sup> )	
S1	16.4	11.5	17.9	-	80.0	10.0	10.0	10.7	19.4	SC-SM
S2	17.8	12.6	21.3	-	79.5	13.0	7.5	10.6	19.7	SC-SM
S3	20.5	14.3	23.2	-	60.0	20.0	20.0	12.1	18.6	SC-SM
S4	22.5	15.1	25.8	-	69.3	19.5	11.3	12.7	19.1	SC
S5	22.7	18.5	25.7	-	28.0	52.0	20.0	15.3	18.3	CL
S6	23.0	15.2	27.6	-	82.8	5.6	11.6	11.7	18.9	SC
S7	23.4	13.3	26.0	25.0	24.0	25.0	26.0	13.2	18.7	CL
S8	23.4	13.3	26.0	25.0	50.0	12.5	12.5	8.6	21.4	SC
S9	28.1	16.5	31.2	-	40.0	30.0	30.0	14.4	17.9	CL
S10	28.5	19.2	31.8	-	38.0	41.0	21.0	21.3	15.4	CL
S11	31.0	18.7	34.5	-	59.0	26.0	15.0	15.5	17.8	SC
S12	31.5	17.4	34.2	-	8.0	62.0	30.0	15.7	18.0	CL
\$13	31.6	18.8	35.8	-	25.0	37.5	37.5	19.0	16.8	CL
S14	34.0	18.3	38.8	-	65.6	11.2	23.2	14.1	18.5	SC
S15	36.1	21.4	39.0	-	20.0	40.0	40.0	18.3	16.9	Cl
S16	37.2	23.6	41.2	-	48.8	32.5	18.8	20.0	16.6	CI
SI/	38.5	29.4	41.5	-	22.0	65.0	13.0	20.2	16.0	CI
S18	40.8	26.0	45.0	-	22.0	71.0	7.0	22.2	16.7	CI
519	41.0	25.0	44.2	-	-	48.0	52.0	22.5	15.8	CI
520	41.2	25.7	44.2	-	-	20.0	50.0	22.7	15.8	CI
521	42.2	20.8	47.2	-	38.5	39.0	22.5	25.7	15./	CI
522	42.5	19.1	44.5	25.0	52.0	21.5	11.2	10.5	17.8	SC
525 524	42.5	19.1	44.5	25.0	55.0 49.4	10.8	24.9	10.1	20.5	SC
524 525	40.0	23.5	49.5	-	48.4	10.8	34.8 25.0	18.2	17.5	CI
525 526	40.5	20.2	49.2 52.0	-	10.0	49.0	42.0	22.5	10.7	CI
S20	49.8 51.0	36.0	55.0	-	10.0	42.0	30.0	27.5	14.4	мн
S27	52.5	31.9	54.5	-	28.3	45.5	26.3	25.8	14.9	CH
S20	54.5	34.1	57.0	28.0	16.0	18.0	38.0	29.0	15.3	мн
S2)	55.0	35.7	58.5	-	18.0	52.0	30.0	31.5	13.5	MH
S31	56.6	21.2	58.4	_	17.0	45.0	38.0	22.9	15.9	СН
S32	57.4	27.2	60.8	_	34.0	32.3	33.8	21.3	16.5	СН
S33	57.5	35.3	60.2	-	-	67.0	33.0	25.1	15.8	МН
\$34	60.5	30.7	63.0	-	8.0	32.0	60.0	23.4	15.5	СН
S35	60.5	47.7	60.0	_	5.0	76.0	19.0	33.5	14.4	МН
S36	60.7	47.7	60.0	-	5.0	76.0	19.0	33.5	14.4	MH
S37	66.4	28.4	68.5	-	31.2	22.4	46.4	23.7	15.9	СН
S38	70.7	26.4	71.6	25.0	23.0	15.0	35.0	26.5	15.5	CV
S39	70.7	19.9	71.6	25.0	50.0	7.5	17.5	16.7	17.3	SC
S40	71.0	35.0	73.0	-	14.0	28.0	58.0	29.1	14.4	MV
S41	74.5	36.1	75.0	-	12.0	43.0	45.0	29.1	14.3	MV
S42	84.9	48.7	86.0	-	-	46.0	54.0	35.1	13.3	MV
S43	95.5	37.5	98.3	-	25.0	22.5	52.5	36.5	12.8	CV
S44	97.0	63.5	97.0	-	10.0	24.0	66.0	48.0	11.8	MV
S45	97.5	48.0	98.2	-	-	20.0	80.0	37.5	11.5	MV
S46	124.0	49.9	121.4			30.0	70.0	44.3	11.8	MV

Table 2 Soil properties and compaction parameters

Note: <sup>1</sup>G:Gravel, S<sup>2</sup>:Sand, M<sup>3</sup>: Silt, C<sup>4</sup>:Clay

tests carried out as part of this study. Before the standard compaction tests, the plastic and liquid limits of the soils containing different proportions of fine sand were determined. The PL is defined as the minimum water content at which soils can deform plastically. Therefore, the optimum water content required for maximum density in cohesive soils is expected to be equal to or less than the PL. For an ideal compaction curve, water contents above the PL also need to be considered. All compaction tests were performed at 6 different water contents. These water contents were defined as 40%, 55%, 70%, 85%, 95%, and 110% of the PL.

Before the compaction test, samples were stored in the humidity cabinet for 24 h. This methodology aims to attain a more homogeneous distribution of water content. After these procedures, compaction curves were generated for each soil sample, and compaction parameters (OWC and MDW) were derived from these curves. It has been observed that the optimum water content is generally in the range of 0.7 times PL to 0.95 times PL.

## **3** Results and discussion

The results of the experimental studies are presented in comparison with a comprehensive database from the literature. Particular attention was paid to ensuring that the consistency limits and grain size distribution of the soils in the database were similar to the soil properties used in this study.

## 3.1 Consistency limits

In Fig. 5, the  $LL_{CUP}$  and  $LL_{FC}$  are presented together with the studies in the literature [35, 37–39, 40–49].

The primary distinction between the traditional Casagrande method and the fall cone test pertains to the precision and reliability of the measured liquid limits. The Casagrande method is predicated on groove closure under repeated impacts, making it operator-dependent and susceptible to variability. Conversely, the fall cone test offers a more objective and replicable measurement by quantifying the penetration depth under a standardised cone weight. In this study, the liquid limit of each soil sample was measured twice. For samples with a LL(%) below 100%, the Casagrande method exhibited a variation of approximately 2%, while the fall cone test demonstrated a variation of around 0.5%. This finding indicates the fall cone test's higher precision and reliability. Fig. 5 (a) shows that for soils with LL less than 100%, the two LL values are close to each other, and in most



Widjaja and Nirwanto [38]

Fig. 5 Comparison of the  $LL_{CUP}$  and  $LL_{FC}$  obtained (a)  $LL_{FC} < 100\%$ , (b)  $LL_{FC} \ge 100\%$ 

cases, the  $LL_{CUP}$  is either equal to or less than the  $LL_{FC}$ . A total of 193 soils were evaluated, employing 78 soils for this study (Fig. 5 (a)). More specifically, Di Matteo [35], Mohajerani [37], Widjaja and Nirwanto [38], Ibrahim and Noori [39], Jain et al. [40], Karakan and Demir [41, 42],

Farias and Llano Serna [43], Evans and Simpson [44], Wang et al. [45], Sampson and Netterberg [46], Campbell [47], Sherwood and Ryley [48] have a total of 9, 2, 5, 16, 15, 1, 3, 3, 6, 11, 6, 13, 25 soils, respectively. Additionally, the number of samples with  $LL_{FC}$  less than 100% is not only considerably high, but the liquid limits also vary within a wide range. However, for soils with  $LL_{FC}$  equal to or greater than 100%, the  $LL_{CUP}$  is prone to be greater than the  $LL_{FC}$ , and the difference between them rises with the increase in the liquid limits, as shown in Fig. 5 (b), but the number of samples is very limited. In particular, 5 out of 39 soils belong to this study, as shown in Fig. 5 (b). For those where the  $LL_{FC}$  is more significant than 100%, Mohajerani [37], Vardanega et al. [49], Widjaja and Nirwanto [38], Karakan and Demir [41, 42], Evans and Simpson [44] have 1, 16, 4, 5, 1 and 7 soils respectively. In addition, in Fig. 5,  $R_1^2$  values represent the correlation coefficient calculated by including the soils in this study, while the  $R_2^2$  values represent the correlation coefficient calculated using only the literature data. The relevant figures display the two distinct correlation coefficients that were computed.

Within the scope of this study,  $PL_{FC}$  values were determined for 83 soils following the steps detailed in Fig. 3. Fig. 6 illustrates the relationship between  $PL_{FC}$  and PL.

It was found that there is a consistent trend between the PL and  $PL_{FC}$  values obtained from the different methods. The agreement between the regression line and the 1:1 line is high for PI values between 13% and 36%, but the



Fig. 6 The variation between the PL and  $PL_{FC}$  for a total of 83 cohesive soils

regression line moves away from the 1:1 line as higher PL values are considered.

A comparison of liquid limits was obtained from different test methods for this study and the literature. The  $h_p$  depth corresponding to the PL obtained from the *h* vs. *w* relationship of the fall cone test was applied to the studies in the literature using the fall cone at 30° and 80 g. For this purpose, the data for the studies reviewed and the 203 soils used in this study (24 clay and sand mixtures, 2 clay and additive mixtures, 7 clay and clay mixtures, and 170 natural cohesive soils) are presented in Table 3. When reviewing the literature, attention has been paid to ensuring that the LL values of the soils used are close to the LL<sub>FC</sub> of the soils used in this study, and studies involving soils with an LL<sub>FC</sub> greater than 121.4% were not used [35, 39, 42, 44–48, 50–54].

The  $h_p$  corresponding to the PL in the fall cone h and w relationship for the data from different researchers in Table 3 was investigated by the following procedure in Fig. 3, and it was found that the obtained  $h_p$  depths may be different for each study. Noticeably, the  $h_p$  values are exceptionally high in soils containing clay-sand and clay- additive mixtures. In this study, the PL<sub>FC</sub> was determined for each study in Table 3, using the proposed value of  $h_{pave}$  equal to 3 mm, and it was observed that the PL and PL<sub>FC</sub> obtained by two different methods agreed, although there were some outliers, as shown in Fig. 7 [35, 39, 42, 44, 46–48, 50–54].

According to the Unified Soil Classification System (USCS), approximately 594 samples, having 46 soils for this study in the database, were classified as 216 CL, 20 ML, 1 OL, 124 CH, 76 MH, 79 SC, 9 SM, 1 SP, 54 GC, 5 GM, 5 GW, and 4 GP in Table 4 [3, 4, 6, 8–10, 28–30, 32, 33, 36, 55–57]. The liquid limits of these soils range from 16.4% to 121.4%, and the plastic limits are within the range of 8.0% and 63.5%. Furthermore, the OWC values are between 6% and 48%, and MDW values are in the range of 9.6 kN/m<sup>3</sup> and 21.4 kN/m<sup>3</sup>.

Fig. 8 [3, 4, 6, 8–10, 28–30, 32, 33, 36, 55–58] shows a strong trend between the OWC and MDW in a wide range, except for some outliers. A limited number of data, which distorts the general pattern, drastically affects  $R^2$ . Although the  $R^2$  for the relationship between the OWC and MDW is 0.83 when considering all data, it increases to 0.89 when only four sample data were excluded. In addition, the  $R^2$  determined using 590 soils, excluding these four outlier data points in the database, was computed as 0.89, while the  $R^2$  calculated for 544 soils without including the 46 soils used in this study was 0.87. As a result, it was observed that the data used in this study contributed positively to the database and increased the  $R^2$ .

		Count	Count		Th	read roll	ing				Fal	ll cone t	est			
Source	Total	LL <sub>FC</sub> <100	$LL_{\rm FC} \ge 100$	Ave. test		PL (%)			w (%)		Pene	tration (	(mm)		$h_p$ (mm)	
	count	(%)	(%)	points	Max.	Min.	Ave.	Max.	Min.	Ave.	Max.	Min.	Ave.	Max.	Min.	Ave.
This study	83	78	5	6	63.5	12.6	31.3	135.0	7.6	54.3	29.6	1.96	16.9	5.6	1.1	3.0
Di Matteo [35]	6	6	0	12	24.0	18.0	20.2	42.7	25.5	33.5	26.2	14.9	19.8	4.1	1.8	3.1
Feng [50]	5	5	0	12	25.0	19.0	22.7	397.7	21.7	89.1	25.5	3.2	12.3	3.4	2.3	2.8
Harison [51]	7	7	0	6	45.0	38.0	40.1	110.8	47.2	70.4	26.4	5.4	16.1	3.1	2.0	2.5
Sivakumar et al. [52] <sup>*</sup>	16	13	1	4	35.4	16.2	26.7	95.9	30.1	61.5	24.6	15.0	19.4	5.5	1.0	2.3
Ibrahim and Noori [39]	9	9	0	4	34.4	15.8	24.7	66.8	19.3	44.0	26.9	13.7	20.0	12.0	3.0	5.8
Karakan and Demir [42]	20	16	4	5	54.0	18.3	30.8	141.1	14.1	52.4	40.6	3.1	19.5	13.0	1.9	6.3
Evans and Simpson [44]	4	3	1	4	29.0	16.0	24.0	55.2	22.4	37.2	29.8	8.7	19.5	7.3	3.0	4.7
Wang et al. [45]	3	3	0	7	46.3	35.3	42.1	90.0	51.3	68.9	28.4	7.0	14.6	4.5	3.6	4.1
Sampson and Netterberg [46]	6	6	0	8	37.9	18.2	28.2	88.6	19.2	46.1	24.6	0.3	12.5	3.0	1.0	1.8
Campbell [47]	13	13	0	4	44.0	22.0	29.9	51.9	25.8	37.8	26.7	3.5	17.8	12.0	1.3	5.7
Sherwood and Ryley [48]	25	25	0	4	43.0	12.0	23.7	89.0	20.5	48.9	28.7	11.9	19.9	8.0	1.0	2.6
Llano Serna and Contreras [53]	3	3	0	38	36.0	14.0	23.3	91.5	23.6	56.2	39.4	3.7	20.1	3.4	1.0	2.1
Zentar et al. [54]	5	5	0	6	43.6	23.6	37.9	111.4	23.5	68.3	32.0	3.7	19.0	6.8	3.7	5.0

Table 3 The fall cone test results compiled from the literature

\*Although the total number of soils is 16, two are excluded from the evaluation due to non-plastic.



Fig. 7 Comparison of the PL and  $PL_{FC}$  for this study and literature

In Table 3, the soil properties considered in each study differ. Wang et al. [45] focused on three cohesive soils with high plasticity, resulting in higher PL and w values. In contrast, Di Matteo [35] examined six soils with low plasticity, leading to lower PL and w values. Therefore, this study includes soil properties from both low-plasticity and high-plasticity soils, thus facilitating more comprehensive evaluations. Notably, the minimum water content and penetration values in this study are lower than those in other studies. This was done to bring the data in Fig. 3 as close to the Y-axis as possible. The wide range of data selected from the literature allowed for a more comprehensive comparison. Furthermore, the water retention potential and compressibility of soils are influenced by their mineralogical composition, which is closely related to their consistency limits. The significant differences in data values observed in Table 3 are primarily attributed to variations in soil type and consistency limits.

An analysis of the soil properties presented in Table 4 reveals that the majority of researchers investigating the relationship between consistency limits and compaction

Source	Total	i	LL <sub>CUP</sub> (%)			PL (%)		OWC (%)			MDW (kN/m <sup>3</sup> )		
	count	Max.	Min.	Ave.	Max.	Min.	Ave.	Max.	Min.	Ave.	Max.	Min.	Ave.
This Study	46	124.0	16.4	48.9	63.5	11.5	26.7	48.0	8.6	22.2	21.4	11.5	16.4
Nagaraj et al. [3]	42	115.0	24.0	48.5	45.3	17.4	27.9	36.8	9.5	21.5	18.3	12.6	15.7
Blotz et al. [4]	14	62.0	17.0	36.6	24.0	8.0	16.2	25.0	8.9	16.1	20.5	14.9	18.2
Sridharan and Nagaraj [6]	10	73.5	37.0	54.7	51.9	18.0	33.8	44.4	16.2	30.0	17.9	11.1	14.0
Jyothirmayi et al. [8]	9	72.0	41.2	54.7	32.5	20.7	25.7	21.5	16.7	19.2	18.7	12.7	15.9
Ng et al. [9]	9	53.0	41.0	45.6	34.0	26.0	29.0	24.0	13.5	17.9	17.1	14.4	15.9
Saikia et al. [10]	40	56.2	20.8	35.9	29.9	10.0	20.3	31.0	15.1	22.1	18.6	13.8	16.4
Hussain and Atalar [28]	8	76.8	43.2	56.9	25.7	18.0	21.3	22.5	15.5	18.8	19.6	15.6	17.0
Fondjo et al. [29]	15	59.7	40.3	59.7	21.7	17.8	21.7	22.1	17.2	22.1	17.7	15.7	17.7
Al Khafaji [30]	88	66.0	14.0	40.1	29.0	10.0	20.2	26.0	9.0	19.2	18.8	10.5	16.7
Tsegaye et al. [32]	56	97.0	55.4	66.6	41.0	22.0	28.4	37.0	15.5	24.1	17.3	12.3	15.0
Firomsa and Quezon [33]	30	103.0	76.0	88.6	59.0	33.0	47.6	40.0	32.0	35.4	13.8	11.9	12.9
Günaydin [36]	126	56.7	23.1	39.7	29.8	13.7	21.6	26.0	7.6	16.3	20.5	14.0	17.5
Benson and Trast [55]	10	70.0	24.0	43.1	32.0	12.0	17.8	24.0	10.0	16.1	20.4	15.4	17.9
Daniel and Benson [56]	2	55.0	34.0	44.5	28.0	16.0	22.0	29.4	17.5	23.5	17.3	14.4	15.8
Ören [57]	9	92.4	33.4	56.5	42.3	17.5	27.7	36.3	20.0	25.1	16.2	11.8	14.6

Table 4 Consistency limits and compaction parameters compiled from literature studies



Fig. 8 The relationship between compaction parameters for this study and the literature

parameters consider both low-plasticity and high-plasticity soils to ensure a comprehensive assessment. In a similar manner, the present investigation follows the same principle in selecting soil properties. When the studies analysed to constitute the database were evaluated, several approaches were used to estimate compaction parameters from consistency limits. Fig. 9 [10, 28, 29, 33] presents the studies indicating that MDW and OWC values show a correlative relationship with liquid limits. While the  $R^2$  values calculated for these studies show a strong degree of agreement, the equations proposed in Table 5 [10, 27–29, 33] differ slightly.

Several researchers have reported that MDW and OWC values show better correlations with PL than LL, as shown in Fig. 10 [3, 6, 8, 32, 58]. The studies that consider the PL value for the estimation of compression parameters demonstrate a high degree of consistency in their data, both within themselves and in comparison to other studies. Additionally, the equations proposed in Table 6 [3, 6, 8, 58, 59] exhibit notable similarities.

Several researchers highlighted the importance of evaluating the PL and LL together to estimate the MDW and OWC [30–33]. Therefore, the researchers obtained higher  $R^2$  through this approach. While the results presented in Table 7 [10, 30–33] for each study align with the perspectives of the researchers, the  $R^2$  values in Table 5 and Table 6 may be higher.

The equations obtained from database-based regression analysis vary according to the grain size distribution and liquid and plastic limit values of the soils used in each study. In addition, this situation has been extensively



(b)

Fig. 9 The relationship between compaction parameters and liquid limit (a) OWC and  $LL_{CUP}$ , (b) MDW and  $LL_{CUP}$ 





Fig. 10 The relationship between compaction parameters and PL  $\,$ (a) OWC vs. PL, (b) MDW vs. PL

Table 5	Correlations	for	estimation	of	com	paction

Source	Count	OWC (%) vs. LL (%)	R <sup>2</sup>	MDW (kN/m <sup>3</sup> ) vs. LL (%)	$R^2$
This study	46	OWC = $0.33 \text{ LL}_{\text{CUP}} + 5.95$ OWC = $0.35 \text{ LL}_{\text{FC}} + 4.42$	0.79 0.79	$MDW = 20.26 - 0.08 \text{ LL}_{CUP}$ $MDW = 20.65 - 0.08 \text{ LL}_{FC}$	0.71 0.72
Saikia et al. [10]	40	$OWC = 0.42 LL_{CUP} + 7.22$	0.85	$MDW = 20.95 - 0.13 LL_{CUP}$	0.90
Gurtug et al. [27]	106	$OWC = 0.30 LL_{CUP} + 4.00$	0.89	$MDW = 41.97 LL^{-0.127}$	-
Hussain and Atalar [28]	8	$OWC = 0.18 LL_{CUP} + 8.52$	0.91	$MDW = 22.57 - 0.10 LL_{CUP}$	0.82
Fondjo et al. [29]	15	OWC = 9.57 $e^{0.0138 \text{ LL}_{CUP}}$	0.96	MDW = 24.78 $e^{-0.006 \text{ LL}_{\text{CUP}}}$	0.98
Firomsa and Quezon [33]	30	$OWC = 0.28 LL_{CUP} + 10.43$	0.90	$MDW = 19.16 - 0.07 LL_{CUP}$	0.87

Table 6 Correlations for estimation of compaction parameters using PL								
Source	Count	OWC (%) vs. PL (%)	$R^2$	MDW (kN/m <sup>3</sup> ) vs. PL (%)	$R^2$			
This study	46	OWC = 0.75 PL + 2.10 $OWC = 0.63 PL_{FC} + 4.70$	0.91 0.87	MDW = 21.14 - 0.18 PL MDW = 20.49 - 0.15 PL <sub>FC</sub>	0.81 0.76			
Nagaraj et al. [3]	42	OWC = 0.76 PL + 0.14	0.86	MDW = 21.06 - 0.18 PL	0.87			
Sridharan and Nagaraj [6]	10	OWC = 0.83 PL + 2.04	0.97	MDW = 20.41 - 0.19 PL	0.94			
Jyothirmayi et al. [8]	9	$OWC = 12.00 e^{0.018 PL}$	0.84	-	-			
Shimobe et al. [59]	33 33	OWC = 0.77 PL + 3.00 OWC = 0.55 PL + 7.27	0.78 0.93	MDW = 19.39 - 0.02 PL MDW = 17.34 - 0.01 PL	0.80 0.79			
Sivrikaya and Ölmez [58]	75	OWC = 0.77 PL + 0.36	0.73	MDW = 23.90 – 0.28 PL	0.66			

. . . .

	Table	7 Correlations for estimation of compact	ion parame	eters using PL and LL	
Source	Count	OWC (%) vs. LL (%) and PL (%)	$R^2$	MDW (kN/m <sup>3</sup> ) vs. LL (%) and PL (%)	$R^2$
This study	46	$\begin{array}{l} {\rm OWC} = 0.58 \; {\rm PL} + 0.09 \; {\rm LL}_{\rm CUP} + 2.09 \\ {\rm OWC} = 0.49 \; {\rm PL}_{\rm FC} + 0.10 \; {\rm LL}_{\rm FC} + 3.78 \end{array}$	0.93 0.89	$\begin{split} MDW &= 21.15 - 0.13 \ PL - 0.02 \ LL_{\rm CUP} \\ MDW &= 20.78 - 0.10 \ PL_{\rm FC} - 0.03 \ LL_{\rm FC} \end{split}$	0.83 0.78
Saikia et al. [10]	40	OWC = 0.16 PL + 0.35 LL + 6.26	0.86	$MDW = 21.07 - 0.02 \ PL - 0.12 \ LL$	0.90
Al Khafaji [30]	88	OWC = 0.63 PL + 0.24 LL - 3.13	-	MDW = 23.90 - 0.20 PL - 0.08 LL	-
Đoković et al. [31]	72	OWC = 0.32 PL + 0.16 LL + 4.18	0.86	$MDW = 21.00 - 0.05 \ PL - 0.07 \ LL$	0.86
Tsegaye et al. [32]	56	OWC = 0.62 PL + 0.08 LL + 1.49	0.88	MDW = 21.83-0.15 PL - 0.04 LL	0.83
Firomsa and Quezon [33]	30	OWC = 0.23 PL + 0.11 LL + 9.74	0.89	MDW = 17.54-0.03 PL - 0.04 LL	0.75

analysed in the literature through the application of various machine learning techniques to predict soil properties and compaction behaviour. In particular, artificial neural networks (ANNs) have been employed for their capacity to model complex, non-linear relationships between soil characteristics and compaction outcomes. Furthermore, the integration of artificial intelligence (AI)-supported software has enabled the processing and analysis of extensive datasets, facilitating the development of highly accurate predictive models.

## **4** Conclusions

Consistency limits and compaction parameters are important engineering properties for designing various geotechnical applications, particularly where soils are used as construction materials and backfill. It is, therefore, necessary to check these parameters using alternative test methods and correlations available in the literature. This study proposed a modified plastic limit method by considering the relationship between water content and penetration depth derived from fall cone tests for soils with wide grain size distributions and index properties. Compaction parameters with high correlations were estimated using  $LL_{FC}$ and PL<sub>FC</sub> values determined from a single test device. The results are summarised below.

1. Comparing the liquid limits determined from the Casagrande and fall cone tests, the LL<sub>CUP</sub> is lower than the  $LL_{EC}$  for cohesive soils when the  $LL_{CUP}$  is less than 100%. In particular, there is a strong relationship between these two values, with  $R^2$  up to 0.95. In contrast, the  $LL_{CUP}$  is greater than the  $LL_{FC}$  for soils when the  $LL_{CUP}$  is either equal to or higher than 100%, and this margin rises with an increment in the liquid limit. Therefore, the relationship between the LL values weakens and  $R^2$  decreases to 0.83. This finding is generally valid for the soil used in this study and for a large data set compiled from literature studies.

- 2. A new approach has been proposed to determine the plastic limit from the fall cone test. The method was tested on this study's soils and a large data set collected from the literature. The findings showed that the water content corresponding to a 3 mm penetration can be used for the  $PL_{FC}$ . Despite some outliers, a satisfactory coefficient of determination ( $R^2 = 0.76$ ) was achieved between PL and  $PL_{FC}$ .
- 3. A large data set compiled from the literature has shown that the  $h_p$  depths corresponding to PL varied from 1 mm to 5.6 mm. While soils with particularly high  $h_p$  values are typically clay- sand and clay-additive soils, more consistent results have been obtained for naturally cohesive soils.
- 4. In the univariate regression analyses performed for 594 compaction parameters and consistency limits in

the database, the most compatible results for predicting OWC and MDW values were obtained using plastic limit values. In addition, the  $R^2$  values calculated from univariate analyses for this study were 0.81 and 0.91 for PL, and 0.76–0.87 for PL<sub>FC</sub>. These values are consistent with the results reported in the literature.

- 5. Although the  $R^2 = 0.93-0.83$  calculated by evaluating the plastic and liquid limits together in multivariate regression analyses for estimating OWC and MDW represents the optimised case for this study, it is quite close to that of the univariate regression analysis considering PL and PL<sub>EC</sub>.
- 6. Considering the multivariate regression analyses between the consistency limits of the different test methods and the compaction parameters, it was found that the compaction parameters could be calculated with a high  $R^2$  based on the PL<sub>FC</sub> and LL<sub>FC</sub>

#### References

- Casagrande, A. "Notes on the design of the liquid limit device", Géotechnique, 8(2), pp. 84–91, 1958. https://doi.org/10.1680/GEOT.1958.8.2.84
- [2] Olsson, J. "Metod för undersökning av lerors hållfasthetsegenskaper, tillämpad vid de geotekniska undersökningarna vid Statens Järnvägar", (Method for investigating the strength properties of clays, as used in geotechnical investigations by the [Swedish State Railways), Geologiska Förening, Förhandlingar, 43(5), pp. 502–507, 1921. (in Swedish)
- [3] Nagaraj, H. B., Reesha, B., Sravan, M. V., Suresh, M. R. "Correlation of compaction characteristics of natural soils with modified plastic limit", Transportation Geotechnics, 2, pp. 65–77, 2015. https://doi.org/10.1016/j.trgeo.2014.09.002
- [4] Blotz, L. R., Benson, C. H., Boutwell, G. P. "Estimating optimum water content and maximum dry unit weight for compacted clays", Journal of Geotechnical and Geoenvironmental Engineering, 124(9), pp. 907–912, 1998. https://doi.org/10.1061/(ASCE)1090-0241(1998)124:9(907)
- [5] Gurtug, Y., Sridharan, A. "Prediction of compaction characteristics of fine-grained soils", Géotechnique, 52(10), pp. 761–763, 2002.
- https://doi.org/10.1680/geot.2002.52.10.761
  [6] Sridharan, A., Nagaraj, H. B. "Plastic limit and compaction characteristics of finegrained soils", Proceedings of the Institution of Civil Engineers, Ground Improvement, 9(1), pp. 17–22, 2005. https://doi.org/10.1680/grim.2005.9.1.17
- Sivrikaya, O., Togrol, E., Kayadelen, C. "Estimating compaction behavior of fine-grained soils based on compaction energy", Canadian Geotechnical Journal, 45(6), pp. 877–887, 2008. https://doi.org/10.1139/T08-022
- [8] Jyothirmayi, K. H., Gnananandarao, T., Kommu, S. "Prediction of compaction characteristics of soil using plastic limit", International Journal of Research in Engineering and Technology (IJRET), 4(6), pp. 253–256, 2015.

obtained from a single test device, in addition to the equations suggested in the literature.

#### Recommendations

The results of this study were based on experimental data and supported by regression analysis. A comprehensive dataset is available in the literature, which can be used to develop a database for further analysis. Machine learning or AI-based methods could enhance these analyses, reducing the experimental workload and enabling a more comprehensive evaluation of soils with different properties.

#### Acknowledgement

The authors extend their gratitude to Hasan Adiyaman, Asst. Prof. Dr. Serhan Ulukaya, and the staff of the Yildiz Technical University Geotechnical Laboratory for their valuable contributions to this study.

- [9] Ng, K. S., Chew, Y. M., Osman, M. H., Mohamad Ghazali, S. K. "Estimating maximum dry density and optimum moisture content of compacted soils", International Conference on Advances in Civil and Environmental Engineering, B1–8, 2015.
- [10] Saikia, A., Baruah, D., Das, K., Rabha, H. J., Dutta, A., Saharia, A. "Predicting compaction characteristics of fine-grained soils in terms of Atterberg limits", International Journal of Geosynthetics and Ground Engineering, 3(2), 18, 2017. https://doi.org/10.1007/s40891-017-0096-4
- [11] Swedish Standards Commission, SS 027120: Geotechnical testsCone liquid limit, Swedish Standards Commission, Stockholm, 1990.
- [12] Norwegian Standards Association, NS 8002: Geotechnical testingDetermination of liquid and plastic limits by the fall cone method, Norwegian Standards Association, Oslo, 1982.
- [13] The Japanese Geotechnical Society, JGS 0142: Test Method for Liquid Limit of Soils by the Fall Cone, The Japanese Geotechnical Society, Tokyo, 2009.
- [14] Bureau of Indian Standards, IS 2720 (Part 5): Methods of Test for SoilsDetermination of Liquid and Plastic Limit, Bureau of Indian Standards, New Delhi, 1985.
- [15] British Standards Institution, BS 1377-2:1: Methods of test for soils for civil engineering purposesClassification tests, British Standards Institution, London, 1990.
- [16] Standards New Zealand, NZS 4402.2.5: Methods of Testing Soils for Civil Engineering PurposesSoil Classification TestsTest 2.5 Determination of the Cone Penetration Limit, Standards New Zealand, Wellington, 1986.
- [17] Association Française de Normalisation (AFNOR), NF P 94-052-1: Soil: Investigation and TestingAtterberg Limit DeterminationPart
   1: Liquid LimitCone Penetrometer Method, AFNOR, Paris, 1995.
- [18] Ministry of Water Resources of the People's Republic of China, SL 237-007: Code for Test of SoilBoundary Moisture Content Test, China Water & Power Press, Beijing, 1999.

- [19] Gosstandart, GOST 5184-80: SoilsMethods of Laboratory Determination of Physical Characteristics, Gosstandart, Moscow, 1980.
- [20] Standards Australia, AS 1289.3.9.1: Methods of Testing Soils for Engineering Purposes–Method 3.9.1: Soil Classification Tests— Determination of the Cone Liquid Limit of a Soil, Standards Australia, Sydney, 2002.
- [21] Kumapley, N. K., Boakye, S. Y. "The use of cone penetrometers for determination of the liquid limits of soils of low plasticity", In: Balkema, A. A. (ed) Proceedings of the 7th Regional Conference for Africa on Soil Mechanics and Foundation Engineering, Accra, Ghana, 1980, pp. 167–170. ISBN 90-6191-093-5 [online] Available at: https://www.worldcat.org/oclc/6943786
- [22] Japanese Geotechnical Society "JGS 0142–2000 Test method for liquid limit of soils by the fall cone", The Japanese Geotechnical Society Standards, Tokyo, Japan, 2000. [online] Available at: https://www.jiban.or.jp/e/standards/jgs-standards/
- [23] Koumoto, T., Houlsby, G. T. "Theory and practice of the fall cone test", Géotechnique, 51(8), pp. 701–712, 2001. https://doi.org/10.1680/GEOT.2001.51.8.701
- [24] Wood, D. M., Wroth, C. P. "The use of the cone penetrometer to determine the plastic limit of soils", Ground Engineering, 11(3), 1978.
- [25] Jumikis, A. R. "Geology of soils of the Newark (NJ) metropolitan area", Journal of the Soil Mechanics and Foundations Division, 84(2), pp. 1646–1–41, 1958.
- [26] Ring, G., Sallberg, J., Collins, W. "Correlation of compaction and classification test data", Highway Research Bulletin, Highway Research Board, National Research Council, 325, pp. 55–75, 1962.
- [27] Gurtug, Y., Sridharan, A., Ikizler, S. B. "Simplified method to predict compaction curves and characteristics of soils", Iranian Journal of Science and Technology, Transactions of Civil Engineering, 42(3), pp. 207–216, 2018. https://doi.org/10.1007/s40996-018-0098-z
- [28] Hussain, A., Atalar, C. "Estimation of compaction characteristics of soils using Atterberg limits", IOP Conference Series: Materials Science and Engineering, 800(1), 012024, 2020. https://doi.org/10.1088/1757-899X/800/1/012024
- [29] Fondjo, A. A., Theron, E., Ray, R. P. "Estimation of optimum moisture content and maximum dry unit weight of fine-grained soils using numerical methods", Walailak Journal of Science and Technology (WJST), 18(16), 22792, 2021. https://doi.org/10.48048/WJST.2021.22792
- [30] Al-Khafaji, A. N. "Estimation of soil compaction parameters by means of Atterberg limits", Quarterly Journal of Engineering Geology and Hydrogeology, 26(4), pp. 359–368, 1993. https://doi.org/10.1144/GSL.QJEGH.1993.026.004.10
- [31] Đoković, K., Rakić, D., Ljubojev, M. "Estimation of soil compaction parameters based on the Atterberg limits", Mining and Metallurgy Engineering Institute Bor, 4, pp. 1–16, 2013. https://doi.org/10.5937/MMEB1304001D
- [32] Tsegaye, T., Fikre Gebregziabher, H., Abebe, T. "Correlation between compaction characteristics and Atterberg limits of fine grained soil found in Addis Ababa", International Journal of Scientific and Engineering Research, 8(6), pp. 357–364, 2017. https://doi.org/10.13140/RG.2.2.17785.13923

- [33] Firomsa Kabeta, W., Quezon, E. T. "Parametric modelling on the relationships between Atterberg limits and compaction characteristics of fine-grained soils", International Journal of Advanced Research in Engineering and Applied Sciences, 8(7), pp. 1–20, 2019.
- [34] Spagnoli, G., Sridharan, A., Oreste, P., Bellato, D., Di Matteo, L. "Statistical variability of the correlation plasticity index versus liquid limit for smectite and kaolinite", Applied Clay Science, 156, pp. 152–159, 2018.

https://doi.org/10.1016/j.clay.2018.02.001

[35] Di Matteo, L. "Liquid limit of low-to medium-plasticity soils: Comparison between Casagrande cup and cone penetrometer test", Bulletin of Engineering Geology and the Environment, 71(1), pp. 79–85, 2012.

https://doi.org/10.1007/s10064-011-0412-5

- [36] Günaydin, O. "Estimation of soil compaction parameters by using statistical analyses and artificial neural networks", Environmental Geology, 57(1), pp. 203–215, 2009. http://doi.org/10.1007/s00254-008-1300-6
- [37] Mohajerani, A. "A suggested calibration for the cone penetrometer liquid limit", Australian Geomechanics, 34(4), pp. 71–76, 1999.
- [38] Widjaja, B., Nirwanto, A. F. "Effect of various temperatures to liquid limit, plastic limit, and plasticity index of clays", IOP Conference Series: Materials Science and Engineering, 508(1), 012099, 2019.

https://doi.org/10.1088/1757-899X/508/1/012099

- [39] Ibrahim, H. H., Noori, K. M. G. "Determining Casagrande liquid limit values from cone penetration test data", ZANCO Journal of Pure and Applied Sciences, 31(s3), pp. 114–120, 2019.
- [40] Jain, P., Gandhi, J., Trivedi, S., Shukla, R. P. "Comparison between Casagrande method and cone penetrometer method for determination of liquid limit of soil", In: Proceedings of the Indian Geotechnical Conference 2019, City, Singapore, 2021, pp. 39–48. ISBN 978-981-33-6346-5 http://doi.org/10.1007/978-981-33-6346-5 4
- [41] Karakan, E., Demir, S. "Effect of fines content and plasticity on undrained shear strength of quartz-clay mixtures", Arabian Journal of Geosciences, 11(23), 743, 2018. https://doi.org/10.1007/s12517-018-4114-1
- [42] Karakan, E., Demir, S. "Liquid limit determination of various sand-clay mixtures by Casagrande and fall cone test methods", Balıkesir Üniversitesi Fen Bilimleri Enstitüsü Dergisi, 20(2), pp. 361–371, 2018. https://doi.org/10.25092/baunfbed.486389

https://doi.org/10.25092/baunibed.480589

- [43] Farias, M. M., Llano-Serna, M. A. "A simple methodology to obtain critical state parameters of remolded clays under normally consolidated conditions using the fall-cone test", Geotechnical Testing Journal, 39(5), pp. 855–864, 2016. http://doi.org/10.1520/GTJ20150207
- [44] Evans, T. M., Simpson, D. C. "Innovative data acquisition for the fall cone test in teaching and research", Geotechnical Testing Journal, 38(3), pp. 346–354, 2015. http://doi.org/10.1520/GTJ20140236
- [45] Wang, D., Zentar, R., Abriak, N. E., Xu, W. "Shear strength behavior of cement/lime-solidified Dunkirk sediments by fall cone tests and vane shear tests", Geotechnical Testing Journal, 36(1), pp. 1–8, 2013. https://doi.org/10.1520/GTJ20120030

- [46] Sampson, L. R., Netterberg, F. "The cone penetration index: A simple new soil index test to replace the plasticity index", presented at Proceedings of the Eleventh International Conference on Soil Mechanics and Foundation Engineering, San Francisco, CA, USA, Aug, 12–16, 1985.
- [47] Campbell, D. J. "Liquid limit determination of arable topsoils using a drop-cone penetrometer", European Journal of Soil Science, 26(3), pp. 234–240, 1975. http://doi.org/10.1111/J.1365-2389.1975.TB01946.X
- [48] Sherwood, P. T., Ryley, M. D. "An investigation of a cone-penetrometer method for the determination of the liquid limit", Géotechnique, 20(2), pp. 203–208, 1970. http://doi.org/10.1680/GEOT.1970.20.2.203
- [49] Vardanega, P. J., Hickey, C. L., Lau, K., Sarzier, H. D. L., Couturier, C. M., Martin, G. "Investigation of the Atterberg limits and undrained fall-cone shear strength variation with water content of some peat soils", International Journal of Pavement Research and Technology, 12(2), pp. 131–138, 2019. http://doi.org/10.1007/s42947-019-0017-0
- [50] Feng, T.-W. "Fall cone penetration and water content relationship of clays", Géotechnique, 50(2), pp. 181–187, 2000. https://doi.org/10.1680/geot.2000.50.2.181
- [51] Harison, J. A. "Using the BS cone penetrometer for the determination of the plastic limit of soils", Géotechnique, 38(3), pp. 433–438, 1988.

https://doi.org/10.1680/geot.1988.38.3.433

- [52] Sivakumar, V., Glynn, D., Cairns, P., Black, J. A. "A new method of measuring plastic limit of fine materials", Géotechnique, 59(10), pp. 813–823, 2009. http://doi.org/10.1680/GEOT.2011.61.1.88
  - p.//doi.org/10.1080/GEO1.2011.01.1.88

- [53] Llano-Serna, M. A., Contreras, L. F. "The effect of surface roughness and shear rate during fall-cone calibration", Géotechnique, 70(4), pp. 332–342, 2020. http://doi.org/10.1680/JGEOT.18.P.222
- [54] Zentar, R., Abriak, N.-E., Dubois, V. "Fall cone test to characterize shear strength of organic sediments", Journal of Geotechnical and Geoenvironmental Engineering, 135(1), pp. 153–157, 2009. https://doi.org/10.1061/(ASCE)1090-0241(2009)135:1(153)
- [55] Benson, C. H., Trast, J. M. "Hydraulic conductivity of thirteen compacted clays", Clays and Clay Minerals, 43(6), pp. 669–681, 1995. http://doi.org/10.1346/CCMN.1995.0430603
- [56] Daniel, D. E., Benson, C. H. "Water content-density criteria for compacted soil liners", Journal of Geotechnical Engineering, 116(12), pp. 1811–1830, 1990. https://doi.org/10.1061/(ASCE)0733-9410(1990)116:12(1811)
- [57] Ören, A. H. "Estimating compaction parameters of clayey soils from sediment volume test", Applied Clay Science, 101, pp. 68–72, 2014. http://doi.org/10.1016/J.CLAY.2014.07.019
- [58] Sivrikaya, O., Ölmez, A. "Zeminlerin kompaksiyon parametreleri ile indeks özellikleri arasındaki ilişkiler", (Correlations between compaction parameters and index properties of soils), In: Proceedings of the 2nd Geotechnical Symposium, Adana, Türkiye, 2007, pp. 50–64. (In Turkish) [online] Available at: https://zmgm. org.tr/tr/yayinlar/2-geoteknik-sempozyumu
- [59] Shimobe, S., Karakan, E., Sezer, A. "Improved dataset for establishing novel relationships between compaction characteristics and physical properties of soils", Bulletin of Engineering Geology and the Environment, 80(11), pp. 8633–8663, 2021. https://doi.org/10.1007/s10064-021-02456-3